

BENETEAU FIRST 21.0

SPECIFICATIONS			MECHANICAL		INTERIOR			SAILS / RIGGING				
Designer	Groupe Finot		Motor	Not Supplied		Wood Finish-std	Cherry		Sailmaker	Doyle		
Stylist	Groupe Finot		HP	Max 8 Rec.		Stove	Alcohol		I	28' 2"	8.60 m	
Year Introduced	1993		Fuel Tank Capacity			Ice Box Capacity			J	7' 10"	2.16 m	
L.O.A.	21' 0"	6.40 m	Transmission			12V Fridge			P	27' 0"	8.20 m	
L.W.L.	19' 8"	6.03 m	Shaft Diameter			12V Freezer			E	9' 4"	2.80 m	
Beam	8' 2"	2.40 m	Prop Spec			Holding Tank(s)			Sail Area 100%	243 sq ft	22.57 sq m	
Displacement	2420 lb	1097 kg	Gear Reduction			Water Capacity			STD Genoa	110%		
Cockpit Size						Headroom	4' 9"	1.49 m				
Mast Ht over water	34' 1"	10.4 m							Race Rig			
									I			
									J			
									P			
KEELS			ELECTRICAL		HARDWARE							
Swing Keel			Batteries	n/a		Mast Mfr	Z Spar		E			
Keel Up	2' 4"	0.7 m	Alternator			Furler	Cruising		Sail Area 100%			
Keel Down	5' 10"	1.77 m	12V Circuits			Winches	Lewmar					
Weight	770 lb	349 kg	110V Outlets	5		Primary	6C					
			Charger Size			Secondary						
						Maneuvering						
SHIPPING DIMENSIONS			NOTES						PERFORMANCE (Std Rig)			
On Cradle w/STD Keel L x W x H									PHRF Handicap	220		
20' 9" x 8' 2" x 8' 3"	6.4 x 2.49 x 2.54 m								S/A to Displ			
On Cradle (No Keel) L x W x H									Displ/Length			
20' 9" x 8' 2" x 8' 3"	6.4 x 2.49 x 2.54 m								Positive Stability		125	
Mast Length	30' 5"	9.3 m										
Mast Weight	55 lb	24.9 kg										